

DESIGN FEATURES

This series of butterfly valves are used for industrial pipelines, as bi-directional open and close and regulation devices, the adjustment range is from 40°C-90°C full open. Suitable temperature $\geq 80^{\circ}\text{C}$

Features

- Size range DN100-1200mm
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body-Ductile Iron/Cast Iron/Stainless Steel /WCB
- Body Ring-SS420/SS304/SS316
- Disc Ring-EPDM
- Shaft-SS420/SS431/SS316
- Fusion bonded epoxy coating-Min 300 Microns



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



i. 中国合格评定国家认可委员会

ii. CNC 中国合格评定国家认可委员会

iii. 中国合格评定国家认可委员会

iv. 中国合格评定国家认可委员会

v. GB 中国合格评定国家认可委员会 TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW KTW API 6D API609

VI. 中国合格评定国家认可委员会 / 中国合格评定国家认可委员会



COMPANY QUALIFICATION



COMPANY EXHIBITION



□□□□□

□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□
 □□□□□□□hrdraulic□□□□□□ RKSfluid□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□
 □□RKSfluid□□□□□□□□□□□□□□□□

□□□□□□□□□
 □□□□□□□2□5□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□
 □□□□□□□1□□

□□□□□□□□□□□□
 □□□□□100□□□□□□□2□□□□□□□□□□□□□□□□□□□□□□□□
 □□□□□TUV□API□WRAS□CE□ISO□□□□□
 □□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□
 □□RKSfluid□□20□□□□□□□□70□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□