



# RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange



## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



RKSfluid 1997 年 1 月 1 日 正式 注册 成立

公 司 总 部 设 于 中 国 北 京

公 司 在 中 国 各 大 中 心 城 市 均 有 分 公 司

公 司 产 品 均 通 过 国 家 标 准 GB 19846

公 司 产 品 均 通 过 国 际 标 准 RKS 1000

公 司 产 品 均 通 过 国 际 标 准 ISO 9001

公 司 产 品 均 通 过 国 际 标 准 TUV CE ADWO-2000

公 司 产 品 均 通 过 国 际 标 准 ISO 9001 TS API & 等 标 准

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准 “ 国 际 标 准 认 证 中 心 ”

公 司 产 品 均 通 过 国 际 标 准 RKSfluid 1997 年

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准 a

公 司 产 品 均 通 过 国 际 标 准 GB 19846

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准 RKS 1000

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准 ISO 9001

公 司 产 品 均 通 过 国 际 标 准 TUV CE ADWO-2000

公 司 产 品 均 通 过 国 际 标 准 ISO 9001 TS API & 等 标 准

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准

公 司 产 品 均 通 过 国 际 标 准 “ 国 际 标 准 认 证 中 心 ”

公 司 产 品 均 通 过 国 际 标 准



# Our Certificates



□□□□

□□□□□□□□□□□□□□□□  
□□□□□□□□□□□□□□□□

□□□□□□□□□□□□  
□□□□□□□□□□□□ RKSfluid□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□  
□□RKSfluid□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□  
□□□□□□□2~5□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□MOQ  
□□□□□□1□□

□□□□□□□□□□  
□□□□□100□□□□□□□2□□□□□□□□□□□□□□□□  
□□□□□TUV□API□WRAS□CE□ISO□□□□  
□□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□



RSfluid 20 70