



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂

II CNC 加工

III 铸造

IV 锻造

V 符合 GB、TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC WRAS、KTW、API 6D、API609

工厂地址：/ /

## Exhibition Photos



## Our Certificates



□□□□□□□□□□□□□□□□□□  
□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
□□□□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
□□ RKSfluid □□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
□□□□□□□□ 2~5 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□ MOQ  
□□□□□□□□ 1pc □

□□□□□□□□□□□□□□□□□□  
□□□□□ 100 □□□□□□□□ 2 □□□□□□□□□□□□□□□□□□□□□□□□  
□□□□□ TUV □ API □ WRAS □ CE □ ISO □□□□□  
□□□□□ DIN □ ASME □ BS EN □ JIS □ API □ AWWA □

□□□□□□□□□□□□□□□□□□  
□□ RKSfluid □□ 20 □□□□□□□□ 70 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□