

FB (FB)

Dn	l	H2	w	
40	230	139	173	3/8"
50	230	139	173	3/8"
65	290	159	198	3/8"
80	310	179	226	3/8"
100	350	214	265	1/2"
125	400	278	307	1/2"
150	480	333	351	1/2"
200	600	600	436	3/4"
250	700	730	524	1"
300	850	850	606	1"

FB

1. DN+2

2.

3. 4.

4. 64

5.

5. (FB) (RB) (ACD)

6.

6.1 1.1 * PN + 1

bar

6.2 1.5 * PN + 1

bar

6.3 0.2

bar

7. 1000 Hz

8.

9.



COMPANY INFORMATION



I □□□□□□□□□□□□□□□□

II □□□□□□□□□□□□□□□□□□□□□□□□□□□□

III □□□□□□□□□□□□□□□□

IV □□□□□□□□□□□□□□

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



□□□□□□□□□□

□□RKSfluid□□□□□□□□□□□□

□□□□□□□□

□□□□□□□2□5□□□□□□□□□□□□□□□□□□

□□□□

□□□□□□□1□□

□□□□□□□□□□

□□□□□100□□□□□□□2□□□□□□□□□□□□□□

□□□□□TUV□API□WRAS□CE□ISO□□□□

□□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□

□□RKSfluid□□20□□□□□□□□70□□□□□□□□□□□□□□□□□□□□