



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Our Factory



I 工厂拥有先进的生产设备

II 工厂拥有CNC加工中心

III 工厂拥有专业的研发团队

iv 工厂拥有完善的质量管理体系

v 工厂拥有GB、CE、TUV、ISO 9001、ADWO-2000、TS、PED、WRC、WRA、KTW、API 6D、API609等认证

工厂地址：中国浙江省温州市乐清市经济开发区

Four factories



Why choose us



Exhibition Photos



Our Certificates



□□□□

□□□□□□□□□□□□□□□□
 - □□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

- RKSfluid

RKSfluid

D
25

D Moq
A 1PC

- 100
2
Tuv API WRA CE ISO
DIN ASME BS EN JIS API AWWA

RKSfluid
20 70