



- Better sealing effect, prevent leakage
- Easier replace the filter bag, lower operating cost
- Adjustable installation height to meet specific application occasions
- Large effective filtration area and higher filtration efficiency
- Longer filter bag service life
- Reasonable structure, more stable and reliable filtration
- China GB-150, International ASME, CE Pressure Standards



- Filter different chemical **acid** and **alkali** liquids
- No seam, no dead angle, precise specification
- Smooth surface, no groove, no dead angle, easy to clean
- Can withstand **high temperature** and **high pressure**
- High quality, high efficiency, economical & practical





- Suitable for high capacity & large flow filtration
- Provided 3 ~ 24 bags design structure
- Equipped with standard size flange
- Flow from 120 to 960 cubic/hours
- Excellent welding quality, safe and reliable

## Our Factory



## Company Advantages



1. 工厂: 工厂位于中国山东省临沂市, 占地面积约 100,000 平方米, 拥有现代化的生产设备和专业的技术团队。
2. 工厂拥有完善的质量管理体系, 确保产品质量稳定可靠。
3. 工厂通过了 API、AWWA、ASME、BS EN、DIN、JIS、TUV、CE、ISO9001、TS、OHSAS、WRAS 等认证。
4. 工厂拥有完善的质量管理体系, 确保产品质量稳定可靠。



## Exhibition Photos



## Our Certificates





Tel: 024 2318 0188-899  
 Email/Skype: ivory@rksfluid.com  
 Mobile/WhatsApp/Wechat: +86 15140071761  
 Add: Pump & Valve Industrial Park, No. 5 Panwu Road,  
 Liaozhong Dist. Shenyang, Liaoning P.R. China

□□□□  
 Q1□□□□□□□□□□  
 A1□□□□□□□□□□

Q2□□□□□□□□  
 A2□□□□□□5-10□□□□□□□□□□□□□□15-90□□

□□3□□□□□□□□  
 A3□T / T 30□□□□□□□□□□□□□□□□□□□□

Q4□□□□□□□□□□□□□□□□□□□□□□□□

A4 1pc

Q5

A5 100

Q6

A6

Q7

A7 1