

DESIGN FEATURES

This series of butterfly valves are used for industrial pipelines, as bi-directional open and close and regulation devices, the adjustment range is from 40°C-90°C full open. Suitable temperature $\geq 80^{\circ}\text{C}$

Features

- Size range DN100-1200mm
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body-Ductile Iron/Cast Iron/Stainless Steel /WCB
- Body Ring-SS420/SS304/SS316
- Disc Ring-EPDM
- Shaft-SS420/SS431/SS316
- Fusion bonded epoxy coating-Min 300 Microns



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



I 公司总部及生产基地

II 公司研发中心

III 公司营销中心

IV 公司售后服务部

V 公司质量管理体系符合 TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC WRAS、KTW、API 6D、API609

公司通过了 ISO 9001、ISO 14001、OHSAS 18001 认证

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



□□□□

□: □□□□□□□□□□□□□□□□
 □□□□"□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□
 □□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□

□: □□□□□□□□□□
 A □ RKSfluid □□□□□□□□□□□□□□□□

□□□□□□
 A □ □□□□ 2~5 □□□□□□□□□□□□□□□□

□: □□□□□
 □: □□□□ 1 □□

□: □□□□□□□□
 □: □□□ 100% □□□□□2 □□□□□□□□□□□□□□□□
 □□□□□ TUV□API□WRAS□CE□ISO □□□□
 □□□□ DIN□ASME□BS EN□JIS□API□AWWA□

□: □□□□□□□□□□□□□□□□□□
 A □ RKSfluid □□20□□□□□70□□□□□□□□□□□□□□□□□□□□□□□□□□