

RKSfluid®

A key Valve in Flow Control



Butterfly Valve

Ball Valve

Gate Valve

Globe Valve

Check Valve

Pipe Fittings



- Streamlined, minimum noise
- Backflow velocity only 0.2s, Head loss 0.1bar with 2m/s
- EPDM/NBR Rubber fully coated disc
- Anti-erosion design, Self-adjusting ball
- Self-cleaning stem, Long time smooth operation



NPS2-NPS14 (DN50-DN350)



NPS16-NPS24 (DN400-DN600)

| Name | Material |
|------------|----------------------------|
| Body | DIN EN 1563-GJS-500-7 |
| Disc | DIN EN 1563-GJS-500-7+EPDM |
| Spring | AISI 304 |
| O-ring | NBR |
| Stem | AISI 304 |
| Washer | EPDM |
| Nut | AISI 304 |
| Bushes | ASTM B150-B150M C61900 |
| Flow Guide | DIN EN1563-GJS-500-7 |
| Screw | A2 |

Specification

| | |
|-------------|------------------------|
| Size | NPS2-NPS24(DN50-DN600) |
| Pressure | PN10 PN16 PN25 |
| Medium | Fresh water |
| Temperature | 0°C~70°C |

Engineering Projects



Partners



