

# RKSfluid®

## A key Valve in Flow Control



Butterfly Valve

Ball Valve

Gate Valve

Globe Valve

Check Valve

Pipe Fittings



- Streamlined, minimum noise
- Backflow velocity only 0.2s, Head loss 0.1bar with 2m/s
- EPDM/NBR Rubber fully coated disc
- Anti-erosion design, Self-adjusting ball
- Self-cleaning stem, Long time smooth operation

Engineering Projects





## — RKSfluid —

- China standard reference unit, to participate in the development of the relevant valve industry standards.
- We have created a R&D and service center in Houston, Texas, USA.
- GB, German standard, American standard, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRAS WRC, KTW, API 6D, API 609



## Our Factory





## Partners



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06





I

II

III

iv

v GB TUV CE ISO 9001 ADWO-2000 TS PED WRC WRA KTW API 6D API609

VI

### Exhibition Photos



# Our Certificates



□□□□

□□□□□□□□□□□□□□□□□□  
- □□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
- □□□□□□□□Hrdraulic□□□□□ RKSfluid□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
□□RKSfluid□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
□□□□□□□□25□□□□□□□□□□□□□□□□□□□□□□

□□Moq.  
A□□□□□□□□1PC□

□□□□□□□□□□□□□□□□□□  
- □□□□□□100□□□□□□□□□□2□□□□□□□□□□□□□□□  
□□□□□□TUV□API□WRA□CE□ISO□□□□  
□□□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□□□

