



RKSfluid®

A key Valve in Flow Control

Butterfly Valve Ball Valve Gate Valve Globe Valve Check Valve Pipe Fittings

This image is a promotional graphic for RKSfluid. It features a central logo of a stylized eagle with spread wings inside a circular frame. The background is a dark industrial setting with various valves and machinery. The text 'RKSfluid®' is prominently displayed in a light blue, glowing font. Below the logo, the tagline 'A key Valve in Flow Control' is written in a similar font. At the bottom, there are six categories of products, each with a representative image and a label: Butterfly Valve, Ball Valve, Gate Valve, Globe Valve, Check Valve, and Pipe Fittings. The labels are in a light blue box with white text.



DESIGN FEATURES



FEATURES

- ◆ Wafer type double flange butterfly valve
- ◆ Size: DN32–DN2400(NPS1 1/4–NPS96)
- ◆ Design Standard: API, DIN, ASME, ISO, ANSI, GB/T, BS EN, AWWA
- ◆ Connection: Wafer, Lug, U-Section
- ◆ Pressure: PN6–PN10–PN16(Class 150)
- ◆ Temperature: -29°C ~ +120°C
- ◆ Valve seat: NBR, EPDM, Viton, Silicone Rubber
- ◆ Valve stem: SS316, SS304, SS420, SS416
- ◆ Application: Water, Power plant, HVAC, Food, Medicine, Desalination



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve



PTFE Butterfly Valve



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve



PTFE Butterfly Valve



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Our Factory



RKSfluid 1997 年 1 月 1 日 成立，
 是一家专业从事研发、生产、销售
 各种 CNC 精密加工件、
 各种工业阀门、管件、
 各种工业设备、
 各种工业配件、
 各种工业材料 GB 标准

Our Certificates



Exhibition Photos

