- Suitable for viscous liquid, V-shaped gap, flow stability, not easy to block
- High-strength structure, mesh screen without deformation, high safety factor, flexible increase in the number of units
- The outer surface of the filter element is smooth and easy to clean. Automated operation, backwashing consumes less liquid
- Tolerate high-intensity positive and negative pressure
- Precision filtration, accuracy range 25-500 μm
- 304, 316L material, corrosion resistant

Our Factory

Company Advantages

01 21 years of professional experience

02 4 factories

03 Independent research and development team
28 top senior professional researchers

04 2 professional testing centers

05 100% high level ex-factory inspection

06 High quality imported materials

07 2 years quality assurance, repair and replacement

1.□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□PP□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
2.□□□□□□□□□□□□□□□□□□□□□□□□□□
3.□□API□AWWA□ASME□BS EN□DIN□JIS□□□TUV□CE□ISO9001□TS□OHSAS□WRAS□□□
□□□□□□□□□□□R& D□□□□□□□□□□□□□□□□□□

Exhibition Photos

[illegible]

Q1[illegible]
A1[illegible]

Q2[illegible]
A2[illegible]5-10[illegible]15-90[illegible]

[illegible]3[illegible]
A3[illegible]T / T 30[illegible]

Q4[illegible]
A4[illegible]1pc[illegible]

Q5[illegible]
A5[illegible]100[illegible]

Q6[illegible]
A6[illegible]

[illegible]7[illegible]
A7[illegible]1[illegible]