



- **Suitable** for viscous liquid, V-shaped gap, flow stability, not easy to block
- **High-strength** structure, mesh screen without deformation, high safety factor, flexible increase in the number of units
- The outer surface of the filter element is smooth and easy to clean. Automated operation, backwashing consumes less liquid
- Tolerate high-intensity positive and negative pressure
- Precision filtration, accuracy range **25-500**  $\mu\text{m}$
- 304, 316L material, corrosion resistant

# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



1. 100% PP
2. 100%
3. API AWWA ASME BS EN DIN JIS TUV CE ISO9001 TS OHSAS WRAS R& D

### Exhibition Photos



### Our Certificates





**RKSfluid®**

Tel: 024 2318 0188-899

Email/Skype: ivory@rksfluid.com

Mobile/WhatsApp/Wechat: +86 15140071761

Add: Pump & Valve Industrial Park, No. 5 Panwu Road,  
Liaozhong Dist. Shenyang, Liaoning P.R. China

□□□□

Q1□□□□□□□□□□

A1□□□□□□□□□□□□□□

Q2□□□□□□□□

A2□□□□□5-10□□□□□□□□□□□□□□15-90□□

□□3□□□□□□□□

A3□T / T 30□□□□□□□□□□□□□□□□□□□□□□□□

Q4□□□□□□□□□□□□□□□□□□

A4□□□□□□□□1pc□□□□□□□□□□□□□□□□□□□□

Q5□□□□□□□□□□□□□□□□□□

A5□□□□100□□□□□□□□□□□□□□

Q6□□□□□□□□□□□□□□□□

A6□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□7□□□□□□□□□□□□

A7□□□1□□□□□□□□□□□□□□□□□□