



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve




Check Valve



Pipe Fittings

DESIGN FEATURES

- RANGE**
- For CI, DI, STL and AC pipes
 - **DN50-DN1000**
 - The body & gasket fit **9 kinds of pipe** with nominal diameters
 - The saddles – Can be used for **all pipe types**



- RELIABLE**
- **EPDM gasket** to EN681-1, mechanically inserted on Series 1425

- ANTI-CORROSION**
- Epoxy or cathodolysis coating
 - Thickness: Epoxy powder coating of **200-250µm**
 - Temperature : Spraying temperature over **200 °C**. Doesn't fade, even wipe with **diethyl ether**.

MATERIAL

- Epoxy powder:  , Earth Best!
- Nuts: **DACROMET®** or **GEOMET®** , Earth Best!
- Cast iron: **EN-GJS-400-15**, nodularity over **95%**!



APPLICATION SCENARIO



Industrial water application



Hydroelectric generation



Sewage treatment



Water treatment



Water supply and drainage



Water transport



Pipe network in house



Irrigation



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 100% high level ex-factory inspection

II CNC precision processing

III professional testing centers

IV 2 years quality assurance, repair and replacement

V GB, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API 6D, API609

