



- Better sealing effect, prevent leakage
- Easier replace the filter bag, lower operating cost
- Adjustable installation height to meet specific application occasions
- Large effective filtration area and higher filtration efficiency
- Longer filter bag service life
- Reasonable structure, more stable and reliable filtration
- China GB-150, International ASME, CE Pressure Standards



- Filter different chemical **acid** and **alkali** liquids
- No seam, no dead angle, precise specification
- Smooth surface, no groove, no dead angle, easy to clean
- Can withstand **high temperature** and **high pressure**
- High quality, high efficiency, economical & practical



- Suitable for high capacity & large flow filtration
- Provided 3 ~ 24 bags design structure
- Equipped with standard size flange
- Flow from 120 to 960 cubic/hours
- Excellent welding quality, safe and reliable

Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



1. 100% high level ex-factory inspection
2. 2 years quality assurance, repair and replacement
3. API, AWWA, ASME, BS, EN, DIN, JIS, TUV, CE, ISO9001, TS, OHSAS, WRAS, R&D

Exhibition Photos



Our Certificates



RKSfluid®

Tel: 024 2318 0188-899

Email/Skype: ivory@rksfluid.com

Mobile/WhatsApp/Wechat: +86 15140071761

Add: Pump & Valve Industrial Park, No. 5 Panwu Road,
Liaozhong Dist. Shenyang, Liaoning P.R. China

□□□□

Q1□□□□□□□□□□

A1□□□□□□□□□□□□□□

Q2□□□□□□□□

A2□□□□□5-10□□□□□□□□□□□□□□15-90□□

□□3□□□□□□□□

A3□T / T 30□□□□□□□□□□□□□□□□□□□□□□□□

Q4□□□□□□□□□□□□□□□□□□□□

A4□□□□□□1pc□□□□□□□□□□□□□□□□

Q5□□□□□□□□□□□□□□□□

A5□□□□100□□□□□□□□□□□□

Q6□□□□□□□□□□□□□□□□

A6□□□□□□□□□□□□□□□□□□□□□□□□

□□7□□□□□□□□□□□□

A7□□□1□□□□□□□□□□□□□□□□