

## DESIGN FEATURES



### ● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

### ● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



**RELATED PRODUCTS**



**SMALL DIAMETER GATE VALVE**  
DN50-DN300,PN10/16/25



**METAL SEATED GATE VALVE**  
DN350-DN600,PN10/16/25



**LARGE DIAMETER METAL SEATED GATE VALVE**  
DN700-DN2000,PN10/16/25









01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



## COMPANY QUALIFICATION



## COMPANY EXHIBITION



## Partners



### Delivery



### Payment



□□□□

□: □□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□



□: □□□□□□□□□□

A□ RKSfluid □□□□□□□□□□□□□□□□

**D**□□□□□□

A□ □□□□2 ~ 5□□□□□□□□□□□□□□□□□□□□

**D:** □□□

□: □□□□ 1 □□

□: □□□□□□□□

□: □□□ 100% □□□□2 □□□□□□□□□□□□□□□□

□□□□Tuv□Api□Wras□CE□ISO□□□□

□□□□ DIN□ASME□BS EN□JIS□API□Awwa□

□: □□□□□□□□□□□□□□□□

A□ RKSfluid □□20□□□□□70□□□□□□□□□□□□□□□□□□□□