



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

DESIGN FEATURES

DURABLE

- 1 piece non-welded PFA molded DSS Disc stem
- Precision casting WCB/CF8M Bodies

TRIPLE SEAL


- Triple Seal: Spring loaded Mechanical seal, Radial Lip Seal, FPM
- China ONLY ONE Manufacturer 400Mpa Isostatic pressing PTFE seat, consistent density

ANTI-CORROSION

- Material: Epoxy powder: AkzoNobel, Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment



APPLICATION SCENARIO



Industrial water application



Nuclear plant



Petroleum



Steel



Wastewater treatment



Acid-base



Food



Irrigation



Our Factory



Company Advantages



I 100% high level ex-factory inspection

II CNC processing

III 2 professional testing centers

IV 2 years quality assurance, repair and replacement

V GB, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API 6D, API609

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□
□□□□□□□□□□□□ RKSfluid□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□
□□RKSfluid□□□□□□□□□□□□□

□□□□□□□□
□□□□□□□□2~5□□□□□□□□□□□□□□□□□□□

□□MOQ
□□□□□□□□1pc□

□□□□□□□□□□
□□□□□□100□□□□□□□2□□□□□□□□□□□□□□□□
□□□□□□TUV□□API□□WRAS□□CE□□ISO□□□□
□□□□□□DIN□□ASME□□BS EN□□JIS□□API□□AWWA□

□□□□□□□□□□□□□□□□
□□RKSfluid□□20□□□□□□70□□□□□□□□□□□□□□□□□□□□□□□