



Name	Material
Body	GGG50
Disc	GGG40+EPDM
Wedge nut	C48600
Stem	SS431
Bonnet	GT450-10
Gasket	EPDM
Y-ring	EPDM85-90
Fix ring	CuZn21Si3/C69300
Thrust bearing	C69300
Seal ring	EPDM70
O ring	NBR
Retainer ring	POM
Bushing ring	POM
Gland	SS431
Dustproof ring	EPDM85
Disc core	GGG40
Bolt	SS316

## Product Description



Super Anti-corrosion  
Epoxy powder coating **200-250µm**,  
baking varnish over **200°C**,  
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



**Three locking tab** for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



**Male guiding system with composite sliding skate** reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



**Triple seal at the operating stem** to ensure tightness with the test of time (2500 cycles).



**New male composite sliding skate technology** ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

## Design standard

Design standard	BS EN 1171 ANSI
Flange	GB/T 17241.6-2008、 DIN 2633-1975、 BS EN1902-2
Face to face	GB/T 12221-2005、 ISO 5752-1988、 BS EN558-1(F4、 F5)
Test standard	EN12266

## Specification

Size	DN50-900
Pressure	PN10 PN16 class150
Medium	Water
Temperature	0°C~90°C

# PRODUCT DISPLAY



# SHIPPING PACKAGING



## COMPANY INFORMATION



I Geschäftsbereich: Fluid Control-Produkte, Technologie und Umweltschutz-Produkte.

II moderne CNC-Bearbeitungszentren, professionelle Prozesszellen,

Weitbereichsschweißgeräte, automatische Montagelinien und Beschichtung.

III Chinas Standard-Referenzeinheit, bei der Entwicklung von entsprechenden Ventilindustriestandards zu beteiligen.

IV Wir haben ein Forschungs- und Entwicklungszentrum in Houston, Texas, in den USA aufgebaut.

V Produkt-Standard: GB, Deutsche Norm, American Standard, TÜV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI Hauptproduktion: Schmetterlingsventil, Kugelventil, Absperrschieber, Rückschlagventil, Hubventil, Rohrfittings, manuell / pneumatisch / elektrisches Stellglied, Ventiltteile.



# EXHIBITION



# COMPANY INFORMATION



## FAQ

F: Wenn ich Zitat benötigen, welche Informationen brauchen wir?

A: Die Ventile Materialien, Temperatur, Druck, Medium, Appllication-System.

F: Können Sie Aktoren liefern, was Sie haben?

A: pneumatisch, elektrisch, Hrdraulic, Magnetventile. RKSfluid Aktoren annehmen USA-Technologie. Welche Sie brauchen, sagen Sie uns.

Q: Was ist Ihre Produktionskapazität?

A: RKSfluid hat vier Pflanzten, die die Produkte liefern, die Sie benötigen.

F: Vorlaufzeit

A: Normale Produkte haben Vorrat in 2 bis 5 Werktagen. Customized Basis auf Ihrem Bedarf.

F: MOQ

A: 1pc für alle Produkte.



Q: Wie über die Qualitätssicherung?

A: 100% Qualitätsprüfung vor der Auslieferung, 2 Jahre Garantie. Stellen Sie sicher, Ihr System Arbeitssicherheit.

Wir haben TUV, API, WRAS, CE, ISO-Zertifizierung.

Standard entsprechen DIN, ASME, BS EN, JIS, API, AWWA.

F: Wie können Sie qualitativ hochwertigen Service für unsere Kunden?

A: RKSfluid eigene 20 Jahre Erfahrung und mehr als 70 F & E-Ingenieure bieten technische Unterstützung, Modellauswahl und Installationsanleitung für Sie.