

Product Display



Product Dimensions

Horizontal Type Pneumatic Butterfly Valve



| Size | O | G | A | L | H1 | H |
|-------|-------|-----------|-------|-----|-----|-------|
| DN20 | 78.0 | RD44*1/6 | 66.0 | 140 | 89 | 166.5 |
| DN25 | 78.0 | RD52*1/6 | 66.0 | 140 | 89 | 166.5 |
| DN32 | 86.0 | RD58*1/6 | 66.0 | 140 | 89 | 166.5 |
| DN40 | 90.0 | RD65*1/6 | 70.0 | 159 | 105 | 186.0 |
| DN50 | 106.0 | RD78*1/6 | 76.0 | 159 | 105 | 192.0 |
| DN65 | 124.0 | RD95*1/6 | 80.0 | 159 | 105 | 197.0 |
| DN80 | 139.0 | RD110*1/4 | 84.0 | 210 | 122 | 225.0 |
| DN100 | 159.0 | RD130*1/4 | 104.0 | 248 | 135 | 260 |
| DN125 | 185.0 | RD160*1/4 | 130.0 | 248 | 135 | 274.0 |
| DN150 | 225.0 | RD190*1/4 | 150.0 | 315 | 165 | 330.0 |



| Φ | Size | D2 | D1 | L | H1 | H |
|-------|--------|------|------|----|-----|-----|
| Φ 19 | 3/4" | 50.5 | 16.1 | 66 | 205 | 245 |
| Φ 25 | 1" | 50.5 | 22.4 | 66 | 205 | 245 |
| Φ 32 | 1 1/4" | 50.5 | 28.8 | 66 | 205 | 245 |
| Φ 38 | 1 1/2" | 50.5 | 35.1 | 66 | 205 | 245 |
| Φ 45 | 1 3/4" | 64 | 42 | 70 | 210 | 250 |
| Φ 51 | 2" | 64 | 47.8 | 72 | 215 | 255 |
| Φ 57 | 2 1/4" | 77 | 53 | 76 | 220 | 265 |
| Φ 63 | 2 1/2" | 77 | 59.5 | 76 | 225 | 265 |
| Φ 76 | 3" | 91 | 72.2 | 76 | 230 | 285 |
| Φ 89 | 3 1/2" | 106 | 85 | 84 | 235 | 290 |
| Φ 102 | 4" | 119 | 97.6 | 90 | 240 | 295 |



| Size | D1 | D2 | A | H | L |
|-------|-------|-------|-----|-----|---------|
| 19 | 16.1 | 50.5 | 135 | 68 | 66 |
| 25.4 | 22.4 | 50.5 | 135 | 68 | 66 |
| 31.8 | 28.8 | 50.5 | 135 | 68 | 66 |
| 38.1 | 35.1 | 50.5 | 135 | 72 | 66 |
| 45 | 42 | 64 | 135 | 74 | 70 |
| 50.8 | 47.8 | 64 | 135 | 79 | 72 |
| 57 | 53 | 77 | 135 | 83 | 76 |
| 63.5 | 59.5 | 77 | 135 | 86 | 76 |
| 76.2 | 72.2 | 91 | 135 | 96 | 76 |
| 89 | 85 | 106 | 160 | 102 | 84 |
| 101.6 | 97.6 | 119 | 160 | 110 | 90 |
| 108 | 104 | 119 | 160 | 112 | 90 |
| 114 | 110 | 130 | 160 | 112 | 106 |
| 133 | 128 | 145 | 210 | 128 | 122/108 |
| 159 | 153.5 | 183 | 210 | 147 | 132/110 |
| 219 | 214 | 233.5 | 315 | 183 | 134 |
| 273 | 267 | 286 | 315 | 257 | 142 |

Application



Dairy



Drink & Beverage



Enzymes



Pharmaceuticals



Daily Necessaries



Cosmetics

| | |
|-------------------|--|
| Produktname | Sanitäre Absperrklappe aus Edelstahl |
| Größe | DN15-300 |
| Verbindungsende | Schweißen, Clamb, Gewinde, Flansch |
| Standard | DIN, SMS, ISO, RJT, 3A, IDF |
| Abdichtung | EPDM, Viton, Silikon |
| Operationsmethode | Manuell, pneumatisch, elektrisch |
| Maximaler Druck | 10 Bar |
| Arbeitstemp. | -10 °C --- + 120 °C |
| Auswahl handhaben | Vollgriff, Mehrfachposition + Kunststoffgriff, Mehrfachposition + Edelstahlgriff |
| Anwendung | Lebensmittel, Getränke, chemische Industrie usw. |



— RKSfluid —

- China standard reference unit, to participate in the development of the relevant valve industry standards.
- We have created a R&D and service center in Houston, Texas, USA.
- GB, German standard, American standard, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRAS WRC, KTW, API 6D, API 609



Four factories



Partners



Exhibition Photos



Our Certificates



Pneumatischer Sanitärtrieb aus rostfreiem Stahl SS304 für Ventilhygiene