




## Product Display




## Product Dimensions


Horizontal Type Pneumatic Butterfly Valve



| Size  | O     | G         | A     | L   | H1  | H     |
|-------|-------|-----------|-------|-----|-----|-------|
| DN20  | 78.0  | RD44*1/6  | 66.0  | 140 | 89  | 166.5 |
| DN25  | 78.0  | RD52*1/6  | 66.0  | 140 | 89  | 166.5 |
| DN32  | 86.0  | RD58*1/6  | 66.0  | 140 | 89  | 166.5 |
| DN40  | 90.0  | RD65*1/6  | 70.0  | 159 | 105 | 186.0 |
| DN50  | 106.0 | RD78*1/6  | 76.0  | 159 | 105 | 192.0 |
| DN65  | 124.0 | RD95*1/6  | 80.0  | 159 | 105 | 197.0 |
| DN80  | 139.0 | RD110*1/4 | 84.0  | 210 | 122 | 225.0 |
| DN100 | 159.0 | RD130*1/4 | 104.0 | 248 | 135 | 260   |
| DN125 | 185.0 | RD160*1/4 | 130.0 | 248 | 135 | 274.0 |
| DN150 | 225.0 | RD190*1/4 | 150.0 | 315 | 165 | 330.0 |



| Φ    | Size   | D2   | D1   | L  | H1  | H   |
|------|--------|------|------|----|-----|-----|
| Φ19  | 3/4"   | 50.5 | 16.1 | 66 | 205 | 245 |
| Φ25  | 1"     | 50.5 | 22.4 | 66 | 205 | 245 |
| Φ32  | 1 1/4" | 50.5 | 28.8 | 66 | 205 | 245 |
| Φ38  | 1 1/2" | 50.5 | 35.1 | 66 | 205 | 245 |
| Φ45  | 1 3/4" | 64   | 42   | 70 | 210 | 250 |
| Φ51  | 2"     | 64   | 47.8 | 72 | 215 | 255 |
| Φ57  | 2 1/4" | 77   | 53   | 76 | 220 | 265 |
| Φ63  | 2 1/2" | 77   | 59.5 | 76 | 225 | 265 |
| Φ76  | 3"     | 91   | 72.2 | 76 | 230 | 285 |
| Φ89  | 3 1/2" | 106  | 85   | 84 | 235 | 290 |
| Φ102 | 4"     | 119  | 97.6 | 90 | 240 | 295 |



| Size  | D1    | D2    | A   | H   | L       |
|-------|-------|-------|-----|-----|---------|
| 19    | 16.1  | 50.5  | 135 | 68  | 66      |
| 25.4  | 22.4  | 50.5  | 135 | 68  | 66      |
| 31.8  | 28.8  | 50.5  | 135 | 68  | 66      |
| 38.1  | 35.1  | 50.5  | 135 | 72  | 66      |
| 45    | 42    | 64    | 135 | 74  | 70      |
| 50.8  | 47.8  | 64    | 135 | 79  | 72      |
| 57    | 53    | 77    | 135 | 83  | 76      |
| 63.5  | 59.5  | 77    | 135 | 86  | 76      |
| 76.2  | 72.2  | 91    | 135 | 96  | 76      |
| 89    | 85    | 106   | 160 | 102 | 84      |
| 101.6 | 97.6  | 119   | 160 | 110 | 90      |
| 108   | 104   | 119   | 160 | 112 | 90      |
| 114   | 110   | 130   | 160 | 112 | 106     |
| 133   | 128   | 145   | 210 | 128 | 122/108 |
| 159   | 153.5 | 183   | 210 | 147 | 132/110 |
| 219   | 214   | 233.5 | 315 | 183 | 134     |
| 273   | 267   | 286   | 315 | 257 | 142     |

## Application



Dairy



Drink&Beverage



Enzymes



Pharmaceuticals



Daily Necessaries



Cosmetics

|                   |                                                                                  |
|-------------------|----------------------------------------------------------------------------------|
| Produktname       | Sanitäre Absperrklappe aus Edelstahl                                             |
| Größe             | DN15-300                                                                         |
| Verbindungsende   | Schweißen, Clamb, Gewinde, Flansch                                               |
| Standard          | DIN, SMS, ISO, RJT, 3A, IDF                                                      |
| Abdichtung        | EPDM, Viton, Silikon                                                             |
| Operationsmethode | Manuell, pneumatisch, elektrisch                                                 |
| Maximaler Druck   | 10 Bar                                                                           |
| Arbeitstemp.      | -10 °C --- + 120 °C                                                              |
| Auswahl handhaben | Vollgriff, Mehrfachposition + Kunststoffgriff, Mehrfachposition + Edelstahlgriff |
| Anwendung         | Lebensmittel, Getränke, chemische Industrie usw.                                 |



## — RKSfluid —

- China standard reference unit, to participate in the development of the relevant valve industry standards.
- We have created a R&D and service center in Houston, Texas, USA.
- GB, German standard, American standard, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRAS WRC, KTW, API 6D, API 609



### Four factories



## Partners



## Exhibition Photos



## Our Certificates











Pneumatischer Sanitärtrieb SS304 aus rostfreiem Stahl für Sanitärventile