



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Double flange resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange



Short-neck butterfly valve for petroleum

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Our Factory



Die RKS-Flüssigkeit wurde 1997 gegründet. Wir sind ein Produktionslabor sowohl für Gießerei als auch für die mechanische Bearbeitung, das Forschungs- und Entwicklungszentrum und das Qualitätskontrollzentrum. Die Produktionsstätten umfassen numerische Kontrollarbeitszentren, professionelle Verarbeitungszellen, Weitspektrumschweißgeräte, automatische Montage- und Beschichtungsleitungen. Wir haben ein Team für Design, Forschung und

Entwicklung erstellt. Unser neues Testcenter als Public Service Platform-Testcenter in der Provinz Liaoning wird zum Standard-GB der chinesischen Ventilreferenzeinheit, um an der Entwicklung der damit verbundenen Ventilindustriestandards teilzunehmen. Um den Ausbau des Geschäfts ins Ausland und die Integration von Ressourcen zu beschleunigen und den Erfolg des Fluidabsatzes von RKS in den Vereinigten Staaten, Deutschland und Russlands zu unterstützen. Wir haben einen amerikanischen Agenten. Unsere Produktdesignstandards umfassen: GB-, ISO-, Deutsche und amerikanische Standards, von TÜV für CE und ADWO-2000, ISO9001, TS, API, genehmigt. Unsere Produkte: Manuelle, pneumatische und Kugelhähne, Schmetterlingsventile und elektrisch betätigte Gateventile. Ventile prüfen, automatische Steuerventile. Gussteile und Armaturen: Ventilkörper, Hauben, Scheiben, Stiele, Getriebe, Universalgelenke, Flanschadapter, Sattelkappen. Nach jahrelanger Entwicklung verbessern wir weiterhin die Innovation, um "bewährte Technologie, überlegene Funktionen und legendärer Wert" als unsere Produktwertphilosophie einhalten. Kundenzufriedenheit ist unser Geschäftsziel!

Exhibition Photos



Our Certificates

