



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



# Company Advantages



© 2023 RKS Fluid Technology Co., Ltd. All rights reserved.

✓ 21 years of professional experience in CNC manufacturing

✓ Independent R&D team with 28 senior researchers

✓ 100% high-level ex-factory inspection

✓ 2 years quality assurance, repair and replacement

✓ ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API 6D, API 609



A

Q

A HRRRAULIC RKSfluid

Q

A RKSfluid 4

Q

A 2~5

Q MOQ

A 1

Q

A 100 2

TUV API WRAS CE ISO

DIN ASME BS EN JIS API AWWA

Q

A RKSfluid 20 70

2 4 6 IV