Design Features

APPLICATION

- Super large diameters up to DN4000 and beyond! Greater adjustability, greater DN/PN in many challenging projects worldwide
- Fast, efficient installation & dismantlement

CLASSIC & STURDY DESIGN

- AWWA-C219 absolutely leakproof
- Independent gasket
- Perfectly balanced economical & technical superior

HIGHLY CUSTOMIZABLE

- According to customer requirement

DURABLE

- ANTI-CORROSION
- Thickness: Epoxy powder coating of 150-200 μm
- Temperature : Spraying temperature over 200℃. Doesn't fade, even wipe with diethyl ether

MATERIAL

- Epoxy powder: AkzoNobel, Earth Best!
- WRAS, KTW-W270, ACS approved materials
- Cast iron: nodularity over 95%!
- Bolts, nuts & washers: Hot Dip Galvanized or Stainless Steel AISI316-A4

Application Scenario

Our Factory

Company Advantages

01 21 years of professional experience

02 4 factories

03 Independent research and development team
28 top senior professional researchers

04 2 professional testing centers

05 100% high level ex-factory inspection

06 High quality imported materials

07 2 years quality assurance, repair and replacement

Ⅰ□□□□□□□□□□□□□□□□□□□□□□□□□□

Ⅱ□□□CNC□□

□□□□□□□□□□□□□□□□□□□□Ⅲ□□□□□□□□□□□

Ⅳ□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Ⅴ□□□□□GB□□□□□□□□□□□□□□□TUV CE□ISO 9001□ADWO-2000□TS□PED□WRC WRAS□KTW□API 6D□API 609□

Ⅵ□□/□□□□/□□□□□□□□□□□□□□□□□

Exhibition Photos

□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□
A□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□□□□
A□□□□□□□□□□□□□□□ RKSfluid□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□
A□RKSfluid□□□□□□□□□□□□4□□□□□□□□

Q□□□□□□□□
A□□□□□□2□5□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q□MOQ
A□□□□□□1□□

Q□□□□□□□□□□
A□□□□□□100□□□□□□□2□□□□□□□□□□□□□□□□□□□
□□□TUV□API□WRAS□□□□□ISO□□□□□□□□
□□□DIN□ASME□BS EN□JIS□API□AWWA□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□

A□RKSfluid□20□□□□□□□□□70□□□