

## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment



# APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





# COMPANY FACTORY









## COMPANY QUALIFICATION



# COMPANY EXHIBITION



□□□□□□

Q □□□□□□□□□□□□□□□□□□□□□□  
 A □□□□□□□□□□□□□□□□□□□□□□

Q □□□□□□□□□□□□□□□□□□□□□□  
 A □□□□□□□ HRRRAULIC □□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□□□□□□□□□  
 □□□□□□□

Q □□□□□□□□□□□□□□□□  
 A □ RKSfluid □□□□□□□□□□□□□□□□□□□□□□

Q □□□□□□□□□  
 A □□□□□□□ 2~5 □□

Q □ MOQ  
 A □□□□□□□□□ 1 □□□

Q □□□□□□□□□□□□□□□□  
 A □□□□□ 100 □□□□□□□□□□ 2 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□  
 □□□□ TUV □ API □ WRAS □ CE □ ISO □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□  
 □□□□ DIN □ ASME □ BS EN □ JIS □ API □ AWWA □□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q □□□□□□□□□□□□□□□□□□□□□□□□□□  
 A □ RKSfluid □ 20 □□□□□□□□□□ 70 □□□

