

□□□

Fully bore globe pattern design, lowest head loss while fully open
Keep stable working condition even the flow rate close to zero
High sensitive and strength fabric reinforced diaphragm
- 1000000 cycles test between fully close and open with working pressure
- 5 times of working pressure destructive test
Most components are machined by CNC
Fusion bonded epoxy coating process is based on GSK & WIS standard
High standard production test
- Seal test: Low pressure 0.5 bar
High pressure 1.1xPN+1 bar
- Shell test: 1.5xPN+1 bar
- Pressure modulated vibration: +/-0.2 bar
Data collected automatically 1000 times/sec, display with static or dynamic chart
Easy installation, operation and free maintenance
Different materials with WRAS/KTW/NSF/FDA/ACS certification to meet different market

Size	DN40-DN1200
Working Medium	Water
Temperature	0°C~70°C
Material	Ductile Iron/Stainless Steel/Cast Steel/Bronze/Aluminum Alloy
Design Standards	CJ/T 219 & JB/T 10674 & EN 1074-5
Pressure Level	PN10, PN16, PN25
Stress Test Standard	GB/T 13927 & ISO 5208 &EN12266-1
Flange drilling standard	GB17241.6; EN1092-2; ISO7005-2; ANSI / JIS / AS2129
Structure Length	GB 12221 & EN558-1



The 745X dual-chamber multi-function pump control valve is installed at the pump outlet to prevent and eliminate the damage of water hammer to the pipeline system/pump when the pump is turned on/off
When the pump opened, the inlet pressure gradually into the valve cavity, so that the valve slowly open, open speed can be adjusted by the needle valve;
When the pump suddenly power failure or stop pumping, lift-off valve disc in its own gravity, Spring Force after the return of the back end of the water hammer force quickly closed.Prevent the back-end of the high-pressure water hammer on the front of the pump damage. Valve closing speed can be adjusted by needle valve or ball valve.

◎□□□□□□□□□□□□□□□□□□□□□□□□

✓□□□CNC□□

✓□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

✓□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

✓□□□□□GB□□□□□□□□□□□□□□□□□□□□TUV CE□ISO 9001□ADWO-2000□TS□PED□WRC WRAS□KTW□API 6D□API609□

VI□□□□□□ □□□□□□□□, ball valve, gate valve, check valve, globe valves, pipe fittings, manual / pneumatic / electric actuator, valve parts

Exhibition Photos

□□□□□

Q□□□□□□□□□□□□□□□□□□□□□
A□□□□□□□□□□□□□□□□□□□□

Q: Can you provide actuators, what you have?
A□□□□□□□HRRAULIC□□□□□□□□□ RKSfluid□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□

Q□□□□□□□□□□□□□□
A□RKSfluid□□□□□□□□□□□□4□□□□□□□□□□

Q□□□□□□□□
A□□□□□□2~5□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q□MOQ
A□□□□□□□1□□□

Q□□□□□□□□□□
A□□□□100□□□□□□□□2□□□□□□□□□□□□□□□□□□□□□
□□□□TUV□API□WRAS□CE□ISO□□□□□□□

□□□DIN□ASME□BS EN□JIS□API□AWWA□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□□□□□

A□RKSfluid□20□□□□□70□□