

DESIGN FEATURES



● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



RELATED PRODUCTS



SMALL DIAMETER GATE VALVE
DN50-DN300,PN10/16/25



METAL SEATED GATE VALVE
DN350-DN600,PN10/16/25



LARGE DIAMETER METAL SEATED GATE VALVE
DN700-DN2000,PN10/16/25

IV

V GB Tuv CE ISO 9001 ADWO-200 TS PED WRC WRAS KTW API 6D API609



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Q: 鋼製パイプの仕様について?

A: RKSfluid の 400mm の鋼製パイプの仕様について

D: 鋼製パイプ

A 鋼製パイプ 250mm の鋼製パイプの仕様について

D: 鋼製パイプ

A: 鋼製パイプ 1 鋼製パイプ

Q: 鋼製パイプの仕様について?

A: 鋼製パイプ 100% の鋼製パイプ 250mm の鋼製パイプの仕様について

Tuv Api Wras CE ISO の鋼製パイプの仕様について

鋼製パイプ DIN ASME BS EN JIS API Awwa の鋼製パイプの仕様について

Q: 鋼製パイプの仕様について?

A: RKSfluid 20 の鋼製パイプ 70 の鋼製パイプの仕様について