

1.
2.
3.

4. 尺寸规格

尺寸规格 尺寸规格FB					
DN	L	H2	H1	W	接口
40	230	139	85	173	3/8"
50	230	139	85	173	3/8"
65	290	159	95	198	3/8"
80	310	179	102	226	3/8"
100	350	214	112	265	1/2"
125	400	278	127	307	1/2"
150	480	333	145	351	1/2"
200	600	600	172	436	3/4"
250	730	730	205	524	1"
300	850	850	232	606	1 1/2"

安装

1. 尺寸DN2mm
2. 尺寸
3. 尺寸
4. 100尺寸64尺寸
5. 尺寸 (FB)尺寸 (RB)尺寸 (ACD)
6. 尺寸
- 6.1 尺寸: 1.1 * PN 1 Bar
- 6.2 尺寸: 1.5 * PN 1 Bar
- 6.3 尺寸: 0.2 Bar
7. 1000 Hz 尺寸
8. 尺寸

安装

1. 尺寸
2. 尺寸:

24
: 24



COMPANY INFORMATION



- I
- II CNC
- III
- IV
- V GB TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609
- VI



COMPANY QUALIFICATION





Partners



□□□□□□

Q:

[illegible]

Q:

```
00: 0000000000000000 0000 RKfluid 00000000000000000000000000000000
```

Q:

```
00: RKSfluid 00400000000000000000000000000000
```

Q:

[illegible]

□□: MOQ

00: 00000000 1 00

Q

[illegible]

TUV API WRAS CE ISO

□□□DIN□ASME□BS EN□JIS□API□AWWA□□□□

Q:

A: RKSfluid 27 70