

DESIGN FEATURES

VERSATILE & RANGE

- Up to 27mm of tolerance, DN40 ~ DN300 stock reduction
- Allows angular deflection of +/- 5°
- Covering most common pipe materials



USER FRIENDLY

- Economical and applicable
- Easy Operation

OPTIMAL SEALING

- Unique gasket with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- Anti-corrosion
- Thickness: Epoxy powder coating of 200-250µm
- Temperature : Spraying temperature over 200 °C. Doesn't fade, even wipe with diethyl ether

MATERIAL

- Epoxy powder:  , Earth Best!
- Nuts: **DACROMET®** or **GEOMET®**, Earth Best!
- Cast iron: EN-GJS-500-7, nodularity over 95%!



APPLICATION SCENARIO



Industrial water application



Hydroelectric generation



Sewagetreatment



Water treatment



Water supply and drainage



Water transport



Pipe network in house



Irrigation



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

02
4 factories

04
2 professional testing centers

06
High quality imported materials



Advanced Advanced CNC

china

cention

WRC
WRA
KTW
API 6D
API609

VI
R
E
C
O
N
G
E
C
H
A
I
N
G
S
U
P
P
L
I
E
R
/
C
O
M
P
A
C
T
I
V
E
/

Exhibition Photos



Our Certificates



Q
A
Q
A
Q
A
Q
a

Q
A
Q
A
Q
A
Q
a

Q
A
Q
A
Q
A
Q
a

Q
A
Q
A
Q
A
Q
a

Q
A
Q
A
Q
A
Q
a

Quality Management

A_{ccredited} to ISO 9001:2015 Quality Management System

Quality Management

A_{ccredited} to ISO 9001:2015 Quality Management System

Quality Management

A_{ccredited} to ISO 9001:2015 Quality Management System

TUV_® API_® WRA_® CE_® ISO_® 9001:2015

Standard_® DIN_® ASME_® BS EN_® JIS_® API_® AWWA_® 9001:2015

Quality Management

A_{ccredited} to ISO 9001:2015 Quality Management System

Quality Management

A_{ccredited} to ISO 9001:2015 Quality Management System