RKSfluid®
A key Valve in Flow Control
Butterfly Valve
Ball Valve
Gate Valve
Globe Valve
Check Valve
Pipe Fittings

Product Display

This series tilting check valves are suitable to be used at the exit of the pump whose medium is water. It is used to prevent or reduce medium back from water hammer. So it can protect the pipeline system.Suitable temperature ≤ 80℃

TLV TILTING CHECK VALVE (BUTTERFLY CHECK VALVE)
DN100- DN1200, PN10 / 16/25

Features

- Double Flange Tilting Check Valve With Hydraulic damper
- Size range DN100-1200mm
- Standard-ISO/BS/ DIN /AWWA/API
- Tests Standard - BS EN 12266-1
- Body-Ductile Iron / Cast Iron / Stainless Steel / WCB
- Disc-Ductile tron / Cast Iron / Stainless Steel / WCB
- Body Ring -SS420/SS304/SS316
- Retaining Ring - SS420 / SS304 /SS316
- Disc Ring - EPDM
- Shaft -SS420/SS431/SS316
- Fusion bonded epoxy coating- Min 300 Microns

SPECIFICATION		
Nominal pressure (MPa)		1.6
Testing pressure(MPa)	Seal	2.4
	Shell	1.76
Working pressure (MPa)		1.6
Suitable temperature (°c)		<80°c
Suitable medium		Water

TECHNICAL REQUIREMENT

1.Face to face standard: EN 558 Series 14.
2.Flanges standard: BS EN1092-2:1997 PN16.
3.Tests standard: BS EN12266-1:2003 Part 1 Rate A .

MATERIALS OF CONSTRUCTION

No.	Part Name
1	Body
2	Shaft bushes
3	Shaft
4	Cover
5	Retainer ring
6	Disc sealing ring
7	Body sealing ring
8	Disc
9	Weight

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□□DN100-DN1800
□□□PN6□PN10□PN16□□□□150□
□□□-29℃□ +120℃
□□□□□□□□GGG40
□□□□NR□NBR□EPDM□Viton□□□□□□□
□□□□/□□□□□□□□□□□□□□□□□□□□□□□□SS316□SS304□□□□□□□□□□□□□□□□□□□□□□□□
STEM□SS316□SS304□SS420□SS416
□□□□□□API□DIN□ASME□ISO□ANSI□GB/T□BS EN□AWWA
□□□□□CE□WRA□API□ISO9001□2015□OHSAS18001□2007
□□□□□□□□□□□□□□□□HVAC□□□□□□□□□□□□□□

PTFE lined butterfly valve

Resilient seat butterfly valve

Double offset butterfly valve

Triple offset butterfly valve

Ball valve

Pipe fittings

i□□□□□□□□□□□□□□□□□□□□□□□□□□

divanced Advanced CNC□□

relaved□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

us□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

inude□□□□□GB□□□□□□□□□□□□□□TUV CE□ISO 9001□ADWO-2000□TS□PED□WRC WRA□KTW□API 6D□API609□

VI□□ /□□□ /□□□□□□□□□□□□□□□□□□□□

Company Advantages

01 21 years of professional experience

02 4 factories

03 Independent research and development team
28 top senior professional researchers

04 2 professional testing centers

05 100% high level ex-factory inspection

06 High quality imported materials

07 2 years quality assurance, repair and replacement

Exhibition Photos

□□□□□□

Q□□□□□□□□□□□□□□□□□□□□
A□□□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□
A□□□□□□□hrdraulic□□□□□□□□ RKSfluid□□□□□□□USA□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□
A□RKSfluid□□□□□□□□□□□□4□□□□□□□□

Q□□□□□□□
A□□□□□□□2□5□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q□Moq
A□□□□□□□1PC□

Q□□□□□□□□□□
A□□□□100□□□□□□2□□□□□□□□□□□□□□□□□□
TUV□API□WRA□CE□ISO□□□□□□□□
□□din□asme□bs en□jis□api□awwa□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□
A□RKSfluid□□□20□□□□70□□□R□D□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□