

产品特点

1. 结构紧凑，体积小，重量轻

2. 密封性能好，使用寿命长

3. 操作方便，维护简单

4. 耐腐蚀性强

5. 使用寿命长

6. 密封性能好

7. 操作方便

8. 维护简单

9. 密封性能好

10. 使用寿命长

符合EN 558-1、ISO 5752、EN 1092-2、ISO 7005-2等标准



- Streamlined, minimum noise
- Backflow velocity only 0.2s, Head loss 0.1bar with 2m/s
- EPDM/NBR Rubber fully coated disc
- Anti-erosion design. Self-adjusting ball
- Self-cleaning stem, Long time smooth operation

口径	DN50-DN600(NPS2-NPS24)
压力等级	PN10/16/25
温度范围	0°C-80°C
材质	铸钢/铸铜/不锈钢
密封材料	橡胶
执行标准	GB/T 12235-2007
法兰标准	EN 558-1
法兰标准	EN 1092-2



NPS2-NPS14 (DN50-DN350)



NPS16-NPS24 (DN400-DN600)



COMPANY INFORMATION



I 公司位于中国江苏省无锡市

II 公司拥有 CNC 加工中心 能够承接各种精密机械加工业务

III 公司拥有完善的质量管理体系

IV 公司拥有完善的质量管理体系

V 公司拥有 GB 质量管理体系 TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API 609

VI 公司拥有完善的质量管理体系

COMPANY FACTORY



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



