



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Engineering Projects



Product Category





©

✓ CNC

✓

✓

✓ GB TUV CE ISO 9001 ADWO-2000 TS PED WRC WRA KTW API 6D API609

VI

Four factories



Why choose us



- 2 professional testing centers
- 28 senior professional researchers
- Independent research and development team



- 21 years of professional experience
- 100% high level ex-factory inspection
- 2 years quality assurance, repair and replacement

A HRRRAULIC RKSfluid
□□□□□□

Q
A RKSfluid 4

Q
A 2~5

Q MOQ
A 1

Q
A 100 2
TUV API WRAS CE ISO
DIN ASME BS EN JIS API AWWA

Q
A RKSfluid 20 70