

DESIGN FEATURES

This series of butterfly valves are used for industrial pipelines, as bi-directional open and close and regulation devices, the adjustment range is from 40°C-90°C full open. Suitable temperature $\geq 80^{\circ}\text{C}$

Features

- Size range DN100-1200mm
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body-Ductile Iron/Cast Iron/Stainless Steel /WCB
- Body Ring-SS420/SS304/SS316
- Disc Ring-EPDM
- Shaft-SS420/SS431/SS316
- Fusion bonded epoxy coating-Min 300 Microns



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



I 公司位于中国山东省潍坊市昌乐县

II 公司拥有 CNC 加工中心 能够承接各种精密机械加工业务

III 公司拥有完善的质量管理体系

IV 公司拥有完善的质量管理体系

V 公司拥有 GB 质量管理体系 TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609

VI 公司拥有完善的质量管理体系

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



□□□□□□

Q: □□□□□□□□□□□□□□□□□□□□?

A □□□□□□□□□□□□□□□□□□□□□□□□

Q: □□□□□□□□□□?

□□: □□□□□□□□□□□□ □□□ RKSfluid □□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q: □□□□□□□□□□□□?

□□: RKSfluid □□4□□□□□□□□□□□□□□□□□□□□□□□□□□

Q: □□□□□□□□

A □□□□□□2□5□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□: **MOQ**

□□: □□□□□□□ 1 □□

Q□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□: □□□□ 100% □□□□□□2 □□□□□□□□□□□□□□□□□□□□□□□□□□□□

TUV□API□WRAS□CE□ISO□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□DIN□ASME□BS EN□JIS□API□AWWA□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q: □□□□□□□□□□□□□□□□□□□□□□□□□□□□?

A: RKSfluid □□ 27 □□□□□□ 70 □□□