



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment



# APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



# COMPANY FACTORY



# COMPANY INFORMATION



is a leading manufacturer of advanced CNC

divanced Advanced CNC machinery and related

related products and services.

us with a wide range of products and services.

include GB, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRA, KTW, API 6D, API609.

VIETNAM [www.vietnam.com](#) / [www.vietnam.com](#) / [www.vietnam.com](#)



## COMPANY QUALIFICATION



# COMPANY EXHIBITION



□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□

A□□□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□

A□□□□□□□□ hydraulic□□□□□□□□□ RKSfluid□□□□□□□□ USA□□□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□

A□ RKSfluid□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□

A□□□□□□□□□□ 2□5□□

Q□ **Moq**

A□□□□□□□□□□ 1PC□

Q□□□□□□□□□□□□□□□□□□□□□□□□

A□□□□□□□□□□ 100□□□□□□□□□□ 2□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

TUV□API□WRA□CE□ISO□□□□□□□□□□□□

□□din□asme□bs en□jis□api□awwa□□□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□□□

A□ RKSfluid□□□□ 20□□□□□□□□ 70□□□□ R□D□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

