

RKSfluid®

A key Valve in Flow Control



- Streamlined, minimum noise
- Backflow velocity only 0.2s, Head loss 0.1bar with 2m/s
- EPDM/NBR Rubber fully coated disc
- Anti-erosion design, Self-adjusting ball
- Self-cleaning stem, Long time smooth operation

Engineering Projects



Partners





PTFE lined butterfly valve



Resilient seat butterfly valve



Double offset butterfly valve



Triple offset butterfly valve



Ball valve



Pipe fittings

Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 100% high level ex-factory inspection

II CNC 100% high level ex-factory inspection

III 100% high level ex-factory inspection

IV 100% high level ex-factory inspection

V GB 100% high level ex-factory inspection TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API

6D API 609

VI

Exhibition Photos



Our Certificates



問 題 集

Q 問 題 集

A 問 題 集

Q 問 題 集

A 問 題 集 RKSfluid 問 題 集

Q 問 題 集

A RKSfluid 問 題 集 4 問 題 集

Q 問 題 集

A 問 題 集 25 問 題 集

Q MOQ

A 問 題 集 1 問 題 集

Q 問 題 集

A 問 題 集 100 問 題 集 2 問 題 集

問 題 TUV API WRAS 問 題 ISO 問 題

問 題 DIN ASME BS EN JIS API AWWA 問 題

Q 問 題 集

A RKSfluid 20 問 題 集 70 問 題 集