




DESIGN FEATURES



- RANGE**
- For PE and PVC pipes
 - Dimension from **32-400mm**
 - Threaded boss or flange connection
 - Female threaded boss outlets from **1/2" to 2"** or flange outlets from **DN40 to DN150**
 - Steel bolts and washers, M8, M10 or M12, A2 or AISI304

- RELIABLE**
- Saddle and strap fully **screwed tight** together

- ANTI-CORROSION**
- Thickness: **Epoxy powder** coating of **150-200µm**
 - Temperature : Spraying temperature over **200 °C**
Doesn't fade, even wipe with **diethyl ether**

MATERIAL

- Epoxy powder:  , Earth Best!
- Nuts: **DACROMET®** or **GEOMET®** , Earth Best!
- Cast iron: EN-GJS-400-15 or EN-GJS-500-7, nodularity over **95%**!

APPLICATION SCENARIO



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂

II 工厂CNC

III 工厂

IV 工厂

V 工厂GB 工厂TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API 609

VI 工厂

Exhibition Photos



A RKSfluid 20 70