

Product Description



Super Anti-corrosion
Epoxy powder coating 200-250μm,
baking varnish over 200°C,
use material.

AkzoNobel



Free wedge nut, reduces the stem bending forces and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to reduce the risk of bacterial growth.



One piece stainless steel stem in for better resistance to axial load and to with stand higher operating torques.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, prohibiting the introduction of foreign bodies at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Engineering Projects










Product Category















 $\mathsf{IV} = \mathsf{IO} = \mathsf{IO$



Why choose us





Exhibition Photos

















Our Certificates



















 $\mathsf{Q} = \mathsf{Q} =$

ADDDDDDDDDDDDD RKSfluid
Q
Q0000000 A0000002050000000000000000000000
Q_MOQ A1
Q
Q0000000000000000000000000000000000000