





RKSfluid®


A key Valve in Flow Control




Butterfly Valve




Ball Valve




Gate Valve



Globe Valve



Check Valve



Pipe Fittings

DESIGN FEATURES

RANGE

- For DI, AC, PVC and Fibre cement pipes
- Dimension from **32-315mm**



Ductile iron



Fibre
Cement



Poly Vinyl
Chloride

LOW COST

- Structure compact and **convenient operation**

RELIABLE

- **EPDM gasket** to EN681-1
- **Anti-corrosive** coating
- Bichromated bolts on series 790

MATERIAL

- S700 & S750: Grey Cast Iron **EN-GJL-250** Quality
- S790: ductile iron **EN-GJS-400-15** Quality

APPLICATION SCENARIO



Industrial water
application



Hydroelectric
generation



Sewagetreatment



Water treatment



Water supply
and drainage



Water transport



Pipe network
in house



Irrigation



Our Factory



Company Advantages



I 100% high level ex-factory inspection

II CNC precision manufacturing

III 21 years of professional experience

IV 2 years quality assurance, repair and replacement

V GB, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API 6D, API 609

A

Q

A RKSfluid

Q

A RKSfluid 4

Q

A 2 5

Q MOQ

A 1

Q

A 100 2

TUV API WRAS ISO

DIN ASME BS EN JIS API AWWA

Q

A RKSfluid 20 70