

产品概述

产品特点

Diffuser

1

0.2

EN 558-1 ISO 5752 EN 1092-2 ISO 7005-2



- Streamlined, minimum noise
- Backflow velocity only 0.2s, Head loss 0.1bar with 2m/s
- EPDM/NBR Rubber fully coated disc
- Anti-erosion design. Self-adjusting ball
- Self-cleaning stem, Long time smooth operation

规格	DN50 -DN600 NPS2 -NPS24
压力等级	PN10/16/25
温度范围	0 °C +80°C
材质	铸钢
表面处理	喷砂
执行标准	GB/T 12235-2007
法兰标准	EN 558-1
法兰标准	EN 1092-2



NPS2-NPS14 (DN50-DN350)



NPS16-NPS24 (DN400-DN600)



COMPANY INFORMATION



Advanced CNC Machining Center

Advanced CNC Machining Center Professional Process Cells

China

certification

GB American Standard Tuv CE ISO 9001 ADWO-2000 TS PED WRC WRA KTW API 6D API609

VI

COMPANY FACTORY



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



Q

A

Q Moq

A

Q

A

TUV API WRA CE ISO

Standard DIN ASME BS EN JIS API AWWA

Q

A RKSfluid 20 70 RD