



DESIGN FEATURES

VERSATILE & RANGE

- Up to 28mm of tolerance, DN40 ~ DN450 stock reduction
- Allows angular deflection of +/- 3° per gasket
- Covering most common pipe materials



OPTIMAL SEALING

- Unique gasket with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- ANTI-CORROSION
- Thickness: Epoxy powder coating of 200-250µm
- Temperature : Spraying temperature over 200°C
Doesn't fade, even wipe with diethyl ether

MATERIAL

- Epoxy powder:  Earth Best!
- Nuts: **DACROMET®** or **GEOMET®**, Earth Best!
- Cast iron: EN-GJS-500-7, nodularity over 95%
- Flange Adaptors: for most common flange standards. PN10/16/ANSI150 drilled

APPLICATION SCENARIO



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance,
repair and replacement

02
4 factories

04
2 professional testing centers

06

High quality imported materials



I. 工厂概况

II. CNC加工中心及精密制造车间

III. 热处理车间

IV. 涂装车间

V. 质量管理体系：GB/T19001-2008, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API 6D, API609

VI. 展会及客户现场照片

Exhibition Photos



Our Certificates



Q: ISO 9001:2015
A: TÜV Rheinland

Q: ASME B31.1-2018
A: DCC

Q: API Q1
A: RKSfluid USA

Q: API Q2
A: RKSfluid USA

Q: ISO 9001:2015
A: TÜV Rheinland

Q: MOQ
A: 1000

Q: CE
A: 100-200

TUV API WRAS CE ISO
DIN ASME BS EN IIS API AWWA

Q: ROHS
A: Yes

AJRKSfluid 2010-20170 R&D
聚丙烯酸盐-PVC乳液