

















Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16.	ANGLIDELD	/1501D	SV/10V
PINTO/PINTO:	ANDI 1ZJLD	/ IJULD	JULIUN

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10	PN10	/PN16,	ANSI	125LB	/150LB	5K/10	(
-----------------------------------	------	--------	------	-------	--------	-------	---

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat: EPDM, NBR, Viton

Connection:Wafer, Lug

## **Our Factory**







 $\label{eq:cond_gb_double} $$V_{0}=0_0GB_{0}=$ 

## **Exhibition Photos**



















A\_RKSfluid\_\_\_\_\_\_\_4\_\_\_\_4\_\_\_\_\_\_

Q00000000

A000000002050000000000000000000000

 $Q \square MOQ$ 

A000000100

TUV\_API\_WRAS\_CE\_ISO\_\_\_\_\_

DIN\_ASME\_BS EN\_JIS\_API\_AWWA\_\_\_\_\_