



# RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

STANDARD MATERIALS SELECTION

NAME	MATERIAL
Body	Cast Iron Ductile Iron
Disc	Nickel Coated DI / CI Epoxy Coated DI / CI Nylon Coated DI / CI CF8 Stainless Steel CF8M Stainless Steel Duplex Stainless Steel Super Duplex Stainless Steel Aluminum Bronze
Stem	SS410 Stainless Steel SS420 Stainless Steel SS431 Stainless Steel SS304 Stainless Steel SS316 Stainless Steel
Seat	EPDM NBR(BUNA-A) PTFE

TECHNICAL PARAMETERS

NAME	
Size	DN50-DN800(NPS2-NPS32)
Pressure	PN10/PN16(Class 150)
Connection	Wafer, Lug
Flange Drilling	DIN2501 PN10/16 ANSI 150LB, JIS B2210 5K/10K
Other material and dimension on request	



Design Standard

Design Standard	ISO 10631 GB/T 12238 BS EN593 DIN3345 JIS B2032
Face to Face	ISO 5752 GB/T 12221 ASME B16.10 BS558-1 DIN3032 JIS B2002
Flange Standard	ISO 7005 GB/T 17214 ASME B16.1 ASME B16.5 BS EN1092 GB/T 9113 DIN2501 JIS 2211-2212
Top Flange	ISO 5211 GB/T 12223
Pressure Test	ISO 5208 GB/T 13927 API598 BS EN12266 DIN 17480 JIS B2003



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Resilient seat butterfly valve



Double flange resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange





## Our Factory





# Company Advantages



I 21 years of professional experience

II 4 factories

III Independent research and development team  
28 top senior professional researchers

IV 2 professional testing centers

V 100% high level ex-factory inspection

VI High quality imported materials

VII 2 years quality assurance, repair and replacement





Q 请问贵司的产品是否通过了ISO9001认证？

A 是的，我们的所有产品都通过了ISO9001认证。

Q 请问贵司的产品是否通过了API认证？

A 是的，我们的RKSfluid产品通过了API认证，符合API 598标准，适用于北美地区。

Q 请问贵司的产品是否通过了CE认证？

A 是的，我们的RKSfluid产品通过了CE认证，符合EN 10744标准。

Q 请问贵司的产品是否通过了TUV认证？

A 是的，我们的RKSfluid产品通过了TUV认证，符合TUV 2554标准。

Q 请问MOQ是多少？

A 我们的MOQ是1000个。

Q 请问贵司的产品是否通过了ASME认证？

A 是的，我们的RKSfluid产品通过了ASME认证，符合ASME B16.34标准。

TUV API WRAS CE ISO 9001

DIN ASME BS EN JIS API AWWA

Q 请问贵司的产品是否通过了BS EN认证？

A 是的，我们的RKSfluid产品通过了BS EN认证，符合BS EN 10744标准。我们拥有20年的R&D经验，致力于为客户提供高质量的产品。