



RKsfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Introduction



Our Aluminum valve handwheel gearbox, 90° slewing drive device is suitable for butterfly valve, ball valve and plug valve and so on. The aluminum alloy material body after static electricity powder coating has an excellent appearance, strong adhesion/mechanical property and anti-corrosion/wear resistance.

Square: 8/ 9/ 11/ 14/ 17/ 19/ 22/ 27


ISO 5211 Flange Type: F05/ F07/ F09/ F10/ F12/ F14/ F16/ F25

Features



Application Scenario





APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



RKSfluid1997

□ □

[illegible][illegible][illegible]

□□□□□□□□□□□□□□□□□□□□GB□□□

□ □

□□□□□□□□□□□□□□□□RKS□□□□□□□□

[illegible]

GB ISO CE ADWO-2000 TUV

ISO9001 TS API

□ □

[illegible][illegible]

□ □

□□□□□□□□□□□□□□□□ RKSfluid□1997□□□□□□□□□□

--	--	--	--	--	--	--	--	--

□ □

CNC

□ □

[illegible][illegible]

□ □

□□□□□□□□□□□□□□□□RKS□□□□□□□□

[illegible]

☐ GB ☐ ISO ☐ CE ☐ ADWO-2000 ☐ TUV

ISO9001 TS API

[illegible][illegible][illegible][illegible]

□ □

I

II

relevant

IV

V

VI

Exhibition Photos





Q□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□□

Q□□□□□□□

$$Q \sqsubseteq MOQ$$

Q□□□□□□□□□□

TUV API WRAS CE ISO

Q

A RKSfluid 20 R&D