



# RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange





## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



RKSfluid 1997

1. 1997  
 2. 1997  
 3. 1997  
 4. 1997  
 5. 1997  
 6. 1997  
 7. 1997  
 8. 1997  
 9. 1997  
 10. 1997  
 11. 1997  
 12. 1997  
 13. 1997  
 14. 1997  
 15. 1997  
 16. 1997  
 17. 1997  
 18. 1997  
 19. 1997  
 20. 1997  
 21. 1997  
 22. 1997  
 23. 1997  
 24. 1997  
 25. 1997  
 26. 1997  
 27. 1997  
 28. 1997  
 29. 1997  
 30. 1997  
 31. 1997  
 32. 1997  
 33. 1997  
 34. 1997  
 35. 1997  
 36. 1997  
 37. 1997  
 38. 1997  
 39. 1997  
 40. 1997  
 41. 1997  
 42. 1997  
 43. 1997  
 44. 1997  
 45. 1997  
 46. 1997  
 47. 1997  
 48. 1997  
 49. 1997  
 50. 1997  
 51. 1997  
 52. 1997  
 53. 1997  
 54. 1997  
 55. 1997  
 56. 1997  
 57. 1997  
 58. 1997  
 59. 1997  
 60. 1997  
 61. 1997  
 62. 1997  
 63. 1997  
 64. 1997  
 65. 1997  
 66. 1997  
 67. 1997  
 68. 1997  
 69. 1997  
 70. 1997  
 71. 1997  
 72. 1997  
 73. 1997  
 74. 1997  
 75. 1997  
 76. 1997  
 77. 1997  
 78. 1997  
 79. 1997  
 80. 1997  
 81. 1997  
 82. 1997  
 83. 1997  
 84. 1997  
 85. 1997  
 86. 1997  
 87. 1997  
 88. 1997  
 89. 1997  
 90. 1997  
 91. 1997  
 92. 1997  
 93. 1997  
 94. 1997  
 95. 1997  
 96. 1997  
 97. 1997  
 98. 1997  
 99. 1997  
 100. 1997









A RKSfluid 20 70