

球墨铸铁球阀

球墨铸铁球阀

- 球墨铸铁球阀
- 球墨铸铁球阀 1 球墨铸铁球阀

球墨铸铁球阀

球墨铸铁球阀

球墨铸铁球阀

- 球墨铸铁球阀
- 球墨铸铁球阀

球墨铸铁球阀 0.2 球墨铸铁球阀

球墨铸铁球阀

EN 558-1 ISO 5752 EN 1092-2 ISO 7005-2 球墨铸铁球阀



- Streamlined, minimum noise
- Backflow velocity only 0.2s, Head loss 0.1bar with 2m/s
- EPDM/NBR Rubber fully coated disc
- Anti-erosion design. Self-adjusting ball
- Self-cleaning stem, Long time smooth operation

球墨铸铁球阀	DN50-DN600(NPS2-NPS24)
球墨铸铁球阀	PN10/16/25
球墨铸铁球阀	0°C-80°C
球墨铸铁球阀	球墨铸铁球阀
球墨铸铁球阀	球墨铸铁球阀
球墨铸铁球阀	GB/T 12235-2007
球墨铸铁球阀	EN 558-1
球墨铸铁球阀	EN 1092-2



NPS2-NPS14 (DN50-DN350)



NPS16-NPS24 (DN400-DN600)



COMPANY FACTORY



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



