



DESIGN FEATURES

DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂整体规划及建设

II 工厂CNC加工及装配

III 工厂质量管理体系

IV 工厂安全管理体系

V 工厂符合GB、TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC WRAS、KTW、API 6D、API609

VI 工厂环保及节能措施

Exhibition Photos



Our Certificates



Q 貴社はどのような製品を製造していますか？

A 各種流体機械の製造を行っています。

Q 貴社の主要な市場はどこにありますか？

A 主に北米市場で、RKSfluid USAが主要な拠点を設けています。

Q 貴社の製品はどのような規格に準拠していますか？

A RKSfluidの製品は、4つの主要な規格に準拠しています。

Q 貴社の製品はどのような用途に使用されますか？

A 主に2500psiから5000psiの圧力範囲で使用されます。

Q MOQはどのくらいですか？

A 一般的に1台から可能です。

Q 貴社の製品はどのような認証を取得していますか？

A 100以上の製品が、2つの主要な認証を取得しています。

TUV API WRAS CE ISO 9001

DIN ASME BS EN JIS API AWWA

Q 貴社の製品のリードタイムはどのくらいですか？

A RKSfluidは20年以上の経験と70以上のR&D拠点を擁しています。