製品の機能:

100%双方向狭い遮断。

流れの方向への制限なしに設置。

軽量化と全体の寸法を減らします。

低圧損失とエネルギーコストの削減

高いKV / CV値。

飲用水システムなどの清掃や消毒が簡単

セルフクリーニング（残留物は閉じ込められます）。

耐腐食性の耐性

主原料:

名前	材料
体	鋳鉄延性鉄炭素鋼のステンレス鋼アルラム青銅
ディスク	延性鉄炭素鋼のステンレス鋼Al-Bronze
軸	ステンレス鋼MONEL K500
シート	BUNA NBR EPDM VITON PTFE HEPDMネオプレンハイパーロン天然ゴム

技術的なパラメータ:

サイズ	DN32-DN600	DN650-DN2000
作業圧力	16バール	10バール
シェル	24バール	15バール
シール（空気）	6バー	6バー
動作温度	-45℃~+ 150℃	
オペレーティング環境	バラストとビルジシステムの化学処理 淡水化植物掘削装置飲料水 ドライパウダー食品および飲料ガス植物 HAVCマイニング業界の紙産業のサンドシーウォーターシュガー産業 サーモテクニカル水処理排水	

運転方法	ハンドレバーワームギア電気空気圧

包装＆配達:

包装の詳細: 各バルブ＆合板ケースのバブルパック。または顧客の要求に従って。

配達細部: 通常30日後の数量に従って

応用:

1.これらの製品は、主にさまざまな産業自動化プロダクションのパイプラインフロー、圧力および温度制御に使用されます。例えば、電気、ピエタクト、冶金、環境保護、エネルギー管理、FIR-FITING SYSTEMS。

同時にそれらは良好な流体制御特性を有し、単に操作することができる。

3.石油、石炭ガス、化学工学、水処理、火力発電所の冷却水系でも使用されています。

Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K
Size:DN25-DN2400
Body:DI CI
Disc: Stainless steel
Seat :EPDM, NBR, Viton
Connection： Wafer, Lug, Flange

Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K
Size:DN25-DN2400
Body:DI CI
Disc: DI+ Nylon
Seat :EPDM, NBR, Viton
Connection： Wafer, Lug, Flange

Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K
Size:DN25-DN2400
Body:DI CI
Disc: Stainless steel
Seat :EPDM, NBR, Viton
Connection： Wafer, Lug, Flange

Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K
Size:DN25-DN2400
Body:DI CI
Disc: Stainless steel
Seat :EPDM, NBR, Viton
Connection： Wafer, Lug, Flange

Double flange resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB， 5K/10K
Size:DN50-DN1000
Body:DI CI
Disc: Stainless steel
Seat :EPDM, NBR, Viton
Connection： Flange

Short-neck butterfly valve for petroleum

ANSI 125LB/150LB
Top Flange Standard:ISO5211
Size:2"-12"
Body: DI CI
Disc :Stainless Steel
Seat： EPDM, NBR, Viton
Connection:Wafer, Lug

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size:DN50~DN600
Body:Ductile Iron
Disc:Ductile Iron+PTFE
Seat: PTFE
Connection: Wafer, Lug, Flange

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size: DN50~DN600
Body: Ductile Iron
Disc: Ductile Iron+PTFE
Seat: PTFE
Connection: Wafer, Lug, Flange

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size: DN50~DN600
Body: WCB, CF8, CF8M
Disc: CF8+PTFE, CF8M+PTFE
Seat: PTFE
Connection: Wafer, Lug

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size: DN50~DN600
Body: WCB, CF8, CF8M
Disc: CF8+PTFE, CF8M+PTFE
Seat: PTFE
Connection: Wafer, Lug

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size: DN50~DN600
Body: Ductile Iron
Disc: CF8 , CF8M
Seat: PTFE
Connection: Wafer, Lug, Flange

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size: DN50~DN600
Body: WCB
Disc: CF8 +PTFE, CF8 +PFA
Seat: PTFE
Connection: Wafer, Lug, Flange

APPLICATION SCENARIO

Industrial water application

Power plant

Sea water desalination

Water treatment

Water supply and drainage

HAVC

Food and drug

Water transport

Our Factory

RKSfluid[illegible]1997[illegible]
[illegible]
[illegible]CNC[illegible]
[illegible]
[illegible]
[illegible]GB[illegible]

[illegible]

[illegible]RKS[illegible]

[illegible]

[illegible]CE[illegible]ADWO-2000[illegible]TUV[illegible]GB[illegible]ISO[illegible]

ISO9001[illegible]TS[illegible]API[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

◎[illegible]

✓[illegible]CNC[illegible]

✓[illegible]

✓[illegible]

✓[illegible]GB[illegible]TUV CE[illegible]ISO 9001[illegible]ADWO-2000[illegible]TS[illegible]PED[illegible]WRC WRA[illegible]KTW[illegible]API 6D[illegible]API609[illegible]

VI[illegible]/[illegible]/[illegible]

Our Certificates

Exhibition Photos