



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings



PTFE Butterfly Valve



PTFE Butterfly Valve



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve



PTFE Butterfly Valve



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



RKSfluid 1997 年 1 月 1 日 在 中 国 上 海 成 立 有 限 公 司
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备
 公 司 主 营 CNC 加 工 中 心 机 床 及 其 配 件
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备
 L 型 工 业 用 液 体 加 工 设 备 GB 150 标 准
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备 RKS 标 准
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备
 公 司 主 营 GB ISO 9001 标 准 及 CE ADWO-2000 标 准 TUV 标 准
 ISO9001 TS API 标 准 及 其 配 件
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备
 公 司 主 营 各 种 工 业 用 液 体 加 工 设 备

I 型 工 业 用 液 体 加 工 设 备

II 型 CNC 加 工 中 心 机 床 及 其 配 件

III 型 工 业 用 液 体 加 工 设 备

IV 型 工 业 用 液 体 加 工 设 备

V 型 工 业 用 液 体 加 工 设 备 TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609

VI 型 工 业 用 液 体 加 工 设 备 / 工 业 用 液 体 加 工 设 备

Exhibition Photos



Our Certificates



Q 请问贵司的产品是否支持定制服务？

A 是的，我们提供定制服务，以满足您的特殊需求。

Q 请问贵司的产品是否符合美国标准？

A 是的，RKSfluid 符合美国标准，如 API、ASME、NEMA 等。

Q 请问贵司的产品是否支持小批量生产？

A 是的，RKSfluid 支持小批量生产，起订量为 4 台。

Q 请问贵司的产品是否支持非标设计？

A 是的，我们提供非标设计服务，以满足您的特殊需求。

Q 请问 MOQ

A 通常为 1 台。

Q 请问贵司的产品是否支持批量生产？

A 是的，我们支持批量生产，起订量为 100 台。

TUV、API、WRAS、CE、ISO 认证。

DIN、ASME、BS EN、JIS、API、AWWA 认证。

Q 请问贵司的产品是否支持长期供货？

A 是的，RKSfluid 支持长期供货，70 天 R&D 周期。