




- Better sealing effect, prevent leakage
- Easier replace the filter bag, lower operating cost
- Adjustable installation height to meet specific application occasions
- Large effective filtration area and higher filtration efficiency
- Longer filter bag service life
- Reasonable structure, more stable and reliable filtration
- China GB-150, International ASME, CE Pressure Standards



- Filter different chemical **acid** and **alkali** liquids
- No seam, no dead angle, precise specification
- Smooth surface, no groove, no dead angle, easy to clean
- Can withstand **high temperature** and **high pressure**
- High quality, high efficiency, economical & practical



- Suitable for high capacity & large flow filtration
- Provided 3 ~ 24 bags design structure
- Equipped with standard size flange
- Flow from 120 to 960 cubic/hours
- Excellent welding quality, safe and reliable

Our Factory



Company Advantages



1. 100% high level ex-factory inspection
2. 10 years quality assurance, repair and replacement
3. API, AWWA, ASME, BS EN, DIN, JIS, TUV, CE, ISO9001, TS, OHSAS, WRAS
4. R&A, D

Exhibition Photos



Our Certificates



Tel: 024 2318 0188-899

Email/Skype: ivory@rksfluid.com

Mobile/WhatsApp/Wechat: +86 15140071761

Add: Pump & Valve Industrial Park, No. 5 Panwu Road,
Liaozhong Dist. Shenyang, Liaoning P.R. China

□□□□□□

Q1□□□□□□□□□□□□□□□□

A1□□□□□□□□□□□□□□□□□□

Q2□□□□□□□□□□□□

A2□□□□□□□□□□5-10□□□□□□□□□□□□□□□□□□15-90□□

Q3□□□□□□□□□□□□

A3□T / T 30□□□

Q4□□□□□□□□□□MOQ□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

A4 quality. We 1pc

Q5

A5 100

Q6

A6

Q7

A7 1