



DESIGN FEATURES

DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%


ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





APPLICATION SCENARIO



Industrial water
application



Power plant



Sea water
desalination



Water treatment



Water supply
and drainage



HAVC



Food and drug



Water transport



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



©

☒ CNC

[illegible][illegible]

✓ GB TÜV CE ISO 9001 ADWO-2000 TS PED WRC
WRAS KTW API 6D API609

VI [REDACTED] / [REDACTED]

Exhibition Photos





Q

A

Q□□□□□□□□□□□□□□□□
A□RKSfluid□□□□□□□□□□□□4□□□□□□□□□□□□

Q□MOQ
A□□□□□□□1□□□

Q□□□□□□□□□□
A□□□□100□□□□□□□2□□□□□□□□□□□□□□□□□□□□
□□□TUV□API□WRAS□CE□ISO□□□□□□□□
□□□DIN□ASME□BS EN□JIS□API□AWWA□□□□□□□□

