



DESIGN FEATURES

DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂占地面积约 100000 平方米

II 工厂 CNC 加工中心约 100 余台

III 工厂拥有完善的质量管理体系

IV 工厂拥有完善的生产管理体系

V 工厂通过 GB 19001、TUV CE、ISO 9001、ADWO-2000、TS PED、WRC WRAS、KTW、API 6D、API609 认证

VI 工厂拥有完善的质量管理体系 / 生产管理体系 / 环境管理体系

Exhibition Photos



