梱包と配送

販売単位: 1つのオブジェクト

シングルパック: 160X160X100 cm

総重量: 38,000 kg

パッケージ型式: 1個/振動バッグ、バルクパック/フラップバルブ付きバタフライバルブ付きウィングチェックバルブ用木製ケース

納期：

量（ピース）	[]	交渉する
時間）	[]	交渉する

説明

1.シンプルなメカニズムを備えた高度な設計、突然のウォーターハンマーやクイッククローズ時の亀裂を回避するための耐性のあるフロート

2.空気の音速までの、より高い空気速度での吹出しに抵抗する空気力学的メカニズム。

3.衝突を防止し、真空時にケージの周りの適切な穴で簡単に排水できるようにする底部ゴムパッド。外部スクリーン
昆虫や鳥の安全と防止のためのオプションになります。

4.振動、屈曲、フロートの直接閉鎖を防ぐためのアームやレバーはありません。フロートからケージを滑らかにして、フロートを保つ
指定されたガイドレール内を移動します。

5. BS EN 1074-4標準を尊重する

Main Valve-DN50-DN300

Parts List

No.	Part Name	Material	Standard
1	Body	Ductile Iron	EN GJS 500-7
2	Float	Stainless Steel	AISI 304
3	Sealing Arc	Stainless Steel	AISI 304
4	In Hex Bolt	Carbon Steen/ Stainless Steel	G. I/ AISI 304
5	Bonnet	Ductile Iron	EN GJS 500-7
6	Cover	Carbon Steel	AISI 304
7	Screen	Stainless Steel	AISI 304
8	Hex Bolt	Carbon Steen/ Stainless Steel	G. I/ AISI 304
9	Washer	Stainless Steel	AISI 304
*10	Pillar	Aluminum	Commercial
11	O-ring	Rubber	NBR/EPDM
12	Seat	Rubber	NBR/EPDM
13	Nozzle Seat	Rubber	NBR/EPDM
14	Guide Barrel	Stainless Steel	AISI 304
15	Buffer	Rubber	NBR/EPDM
16	Small Nozzle	Stainless Steel	AISI 304

*: For Size ≤DN150.